

## Castrol Hyspin HVI

High viscosity index anti-wear hydraulic oils

### Description

The Castrol Hyspin™ HVI range of high viscosity index (VI) oils is based on a carefully selected ashless (zinc free) additive system designed to meet and exceed the most exacting performance standards.

### Application

Hyspin HVI oils are intended for severely stressed hydraulic systems requiring a high level of anti-wear performance and fine filtration. In addition, Hyspin HVI exhibits excellent corrosion protection as well as outstanding thermal and oxidative stability. Hyspin HVI has excellent hydrolytic stability and separates rapidly from water contamination.

Hyspin HVI contains a shear stable additive system helps maintain the viscosity characteristics of the product over a wide temperature range even during prolonged use and imparts a very low pour point which enables the product to be used in very cold environments.

Applications include:

- Outdoor equipment which are likely to operate in wide temperature ranges, such as machinery subjected to cold start up conditions and high temperature continuous running. Examples include off-highway and marine applications.
- Indoor manufacturing equipment that incorporates control systems requiring minimal viscosity change with temperature. Examples include precision machine tools.

The Hyspin HVI range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers.

Hyspin HVI is classified as follows:

DIN 51502 classification – HVLP

ISO 6743/4 - Hydraulic Oils Type HV

Hyspin HVI grades meet the requirements (for appropriate viscosity grade) of:

DIN 51524 Part 3

Cincinnati Lamb (Milacron) P 68-69-70

Denison (Parker Hannafin) HF-0

US Steel 126 & 127

Eaton (formerly Vickers) I-286-S & M-2950-S

Frank Mohn

Bosch Rexroth RE07075/RE90220

### Advantages

- High viscosity index and low pour point enables the product to be used over a wide temperature range, with good shear stability which means no excessive loss in viscosity due to mechanical shearing.
- Excellent anti-wear performance provides extended wear protection for hydraulic pumps. Reduced down time due to unscheduled maintenance and savings from replacement part costs.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.
- Excellent thermal and oxidative stability provides reliable performance and extended oil life in severe applications. Minimal deposit formation gives a cleaner system and reduced frequency of filter changes.
- Excellent filterability characteristics (including in the presence of water) enables cost savings to be made due to increased filter life.

### Typical Characteristics

Test	Method	Units	HVI 15	HVI 32	HVI 46	HVI 68
ISO Viscosity Grade	-	-	15	32	46	68
Density @ 15°C	ISO 12185/ ASTM D4052	g/ml	0.88	0.88	0.88	0.88
K.V. @ 40°C	ISO 3104/ ASTM D445	mm <sup>2</sup> /s	15	32	46	68
K.V. @ 100°C	ISO 3104/ ASTM D445	mm <sup>2</sup> /s	3.83	6.41	8.32	10.8
Viscosity Index	ISO 2909/ ASTM 2270	-	>150	>150	>150	>140
Pour Point	ISO 3016/ ASTM D97	°C/°F	<-51/<-60	-45/-49	-42/-44	-36/-33
Flash Point, COC	ISO 2592/ ASTM D92	°C/°F	205/401	210/411	215/419	226/440
Flash Point, PMCC	ISO 2719/ ASTM D93	°C	160	200	220	220
Foam Seq I	ISO 6247/ ASTM D892	mls	20/0	20/0	20/0	20/0
Water Separability @ 54°C	ISO 6614/ ASTM D1401	Mins	5	10	15	15
Air Release Value	ISO 9120/ ASTM D3427	Mins	4	4	8	8
FZG fail stage (A8.3/90)	ISO 14635-1/ DIN 51354	-	-	11	12	12
Rust Test (24 hrs Distilled water)	ISO 7210/ ASTM D665A	-	Pass	Pass	Pass	Pass
Rust Test (24 hrs Synthetic sea water)	ISO 7210/ ASTM D665B	-	Pass	Pass	Pass	Pass
K.V. @ 100°C after 4 hours KRL	DIN 51350 T6	% loss	-	-	9.5	-

Subject to usual manufacturing tolerances.

Castrol, Hyspin Other, and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK  
[www.castrol.com/industrial](http://www.castrol.com/industrial)